

Data Sheet

Itemnumber.....: 5522001100



A = 318	AC = 396	BB = 369	DB = M20	EG = 50	GD = 10	HB = 264	L = 769	TL = 192
AA = 70	AD = 313	C = 133	E = 110	F = 16	H = 200	HD = 513	LB = 659	
AB = 388	B = 305	D = 55	EB = 100	G = 49	HA = 25	K = 18,50	TB = 260	

Version

Type.....: HMC3 200L2-2
Design.....: Induction motor
Standard series.....: IEC 60034
Phase / Voltage range.....: 3~ / Low

Electrical design

Efficiency.....: IE3
Pole.....: 2
Power at 50 Hz (kW).....: 37,0
Hz.....: 50
Voltage.....: 400VD/690VY
Winding voltage.....: 400VD/690VY 50 Hz
Power output (kW).....: 37,0
Duty.....: S1
Insulation class.....: F
Temperature rise.....: B

Mechanical design

Frame size.....: 200
Mounting.....: B3
Rain cap.....: No
Protection class.....: IP55
Cooling method.....: IC411/TEFC
External grounding.....: Yes
Drain hole.....: Yes
Frame material.....: Cast Iron
Material approval.....: None
Shaft.....: IEC standard
Key.....: Closed key
Balancing.....: Half key balancing
Vibration class.....: Grade-A
Weight (kg).....: 261

Environment condition

Ambient temp. min. (°C).....: -20
Ambient temp. max. (°C).....: 40
Altitude (mtr up to).....: 1000

Bearing

DE Bearing.....: 6312/C3
NDE Bearing.....: 6312/C3
Fixed bearing.....: DE

Terminal box

Tbox position.....: Top
Cable entry direction.....: Right (from DE)
Cable entry
Main.....: 2 x M50x1,5
Plastic blindcaps
Accessory.....: 2 x M20x1,5
Plastic blindcaps
Terminal board thread.....: 6-M8

Motor protection

Thermal protection main.....: PTC 3x 155 dgr
Thermal protection second.....: None
Space heater.....: None
Temperature detector.....: No
SPM.....: No
IR wire.....: No
Tropical insulation.....: No

Explosion protection

According to.....: None
Type of protection.....: None

General

Direction of rotation.....: CW
Painting.....: RAL 9005
Nameplate.....: Multivoltage
Special packing.....: No
Special requirements.....: No

Test values

Rotor inertia (kgm²).....: 0,22
Noise level (dB(A)).....: 82
No load current (A).....: 16,2
Winding resist. (ohm).....: 0,15
Starting time (sec.).....: 0,18
Temp. rise winding (K).....: 55
Temp. rise surface (K).....: 39

Rated power (kW)	37,0	36,0	44,5	43,0
Frequency (Hz)	50	50	60	60
Voltage (V)	400 Y 690	380 660	480 830	440 D
Connection	D Y	D Y	D Y	D
Full load current (A)	62,5 36,0	64,5 37,5	62,5 36,0	64,5
Speed (rpm)	2970	2970	3560	3560
Power factor cos(phi)	0,91	0,92	0,91	0,92
Efficiency, 100/75/50 (%)	93,7/ 93,7 /92,7	93,7/ 93,7 /92,7	93,7/ 93,7 /92,7	93,3/ 93,2 /92,2
Ist/In	9,05	7,95	9,05	8,30
Full load torque (Nm)	118	116	118	116
Tst/Tn	3,65	3,35	3,65	3,15
Tmax/Tn	3,65	3,40	3,65	3,15
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45