


# Data Sheet

Itemnumber..... 5523550200



AC = 699	DB = M24	EG = 56	GD = 12	LA = 25	N = 680	T = 6
AD = 664	E = 140	F = 20	HB = 489	LB = 1367	P = 800	TB = 460
D = 75	EB = 130	G = 67,50	L = 1507	M = 740	S = 8-Ø24	TL = 330

## Version

Type..... HMC3 355M-2  
Design..... Induction motor  
Standard series..... IEC 60034  
Phase / Voltage range..... 3~ / Low

## Electrical design

Efficiency..... IE3  
Pole..... 2  
Power at 50 Hz (kW)..... 250  
Hz..... 50  
Voltage..... 400VD/690VY  
Winding voltage..... 400VD/690VY 50 Hz  
Power output (kW)..... 250  
Duty..... S1  
Insulation class..... F  
Temperature rise..... B

## Mechanical design

Frame size..... 355  
Mounting..... B5  
Rain cap..... No  
Protection class..... IP55  
Cooling method..... IC411/TEFC  
External grounding..... Yes  
Drain hole..... Yes  
Frame material..... Cast Iron  
Material approval..... None  
Shaft..... IEC standard  
Key..... Closed key  
Balancing..... Half key balancing  
Vibration class..... Grade-A  
Weight (kg)..... 1.569

## Environment condition

Ambient temp. min. (°C)..... -20  
Ambient temp. max. (°C)..... 40  
Altitude (mtr up to)..... 1000

## Bearing

DE Bearing..... 6319/C3  
NDE Bearing..... 6319/C3  
Fixed bearing..... DE

## Terminal box

Tbox position..... Top  
Cable entry direction..... Right (from DE)  
Cable entry  
Main..... 2 x M72x2,0  
Metal blindcaps  
Accessory..... 2 x M20x1,5  
Metal blindcaps  
Terminal board thread..... 6-M16

## Motor protection

Thermal protection main..... PTC 3x 155 dgr  
Thermal protection second.. None  
Space heater..... None  
Temperature detector..... No  
SPM..... No  
IR wire..... No  
Tropical insulation..... No

## Explosion protection

According to..... None  
Type of protection..... None

## General

Direction of rotation..... CW  
Painting..... RAL 9005  
Nameplate..... Multivoltage  
Special packing..... No  
Special requirements..... No

## Test values

Rotor inertia (kgm²)..... 3,59  
Noise level (dB(A))..... 90  
No load current (A)..... 116  
Winding resist. (ohm)..... 0,0074  
Starting time (sec.)..... 0,93  
Temp. rise winding (K)..... 78  
Temp. rise surface (K)..... 47

Rated power (kW)	250	242	300	290
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	415 242	430 248	415 242	430
Speed (rpm)	2980	2980	3580	3580
Power factor cos(phi)	0,90	0,91	0,90	0,91
Efficiency, 100/75/50 (%)	95,8/ 96,0 /95,5	95,8/ 96,0 /95,5	95,8/ 96,0 /95,5	95,5/ 95,7 /95,2
Ist/In	6,70	5,90	6,70	6,15
Full load torque (Nm)	800	775	800	775
Tst/Tn	1,72	1,60	1,72	1,48
Tmax/Tn	2,30	2,14	2,30	2,00
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45