


Data Sheet

Itemnumber.....: 6042000400



A = 318	AC = 397	BB = 369	DB = M20	EG = 52	GD = 10	HB = 170	L = 774	M = 350	S = 4-Ø18,5	TL = 250
AA = 70	AD = 296	C = 133	E = 110	F = 16	H = 200	HD = 496	LA = 17	N = 300	T = 5	
AB = 384	B = 305	D = 55	EB = 100	G = 49	HA = 25	K = 18,50	LB = 664	P = 400	TB = 200	

Version

Type.....: HMC4 200L-4
Design.....: Induction motor
Standard series.....: IEC 60034
Phase / Voltage range.....: 3~ / Low

Electrical design

Efficiency.....: IE4
Pole.....: 4
Power at 50 Hz (kW).....: 30,0
Hz.....: 50
Voltage.....: 400VD/690VY
Winding voltage.....: 400VD/690VY 50 Hz
Power output (kW).....: 30,0
Duty.....: S1
Insulation class.....: F
Temperature rise.....: B

Mechanical design

Frame size.....: 200
Mounting.....: B35
Rain cap.....: No
Protection class.....: IP55
Cooling method.....: IC411/TEFC
External grounding.....: Yes
Drain hole.....: Yes
Frame material.....: Cast Iron
Material approval.....: None
Shaft.....: IEC standard
Key.....: Closed key
Balancing.....: Half key balancing
Vibration class.....: Grade-A
Weight (kg).....: 265

Environment condition

Ambient temp. min. (°C).....: -20
Ambient temp. max. (°C).....: 40
Altitude (mtr up to).....: 1000

Bearing

DE Bearing.....: 6312/C3
NDE Bearing.....: 6212/C3
Fixed bearing.....: DE

Terminal box

Tbox position.....: Top
Cable entry direction.....: Right (from DE)
Cable entry
Main.....: 2 x M50x1,5
Plastic blindcaps
Accessory.....: 2 x M20x1,5
Plastic blindcaps
Terminal board thread.....: M8

Test values

Rotor inertia (kgm²).....: 0,31
Noise level (dB(A)).....: 70
Starting time (sec.).....: 0,10

Motor protection

Thermal protection main.....: PTC 3x 155 dgr
Thermal protection second..: None
Space heater.....: None None
Temperature detector.....: No
SPM.....: No
IR wire.....: No
Tropical insulation.....: No

Explosion protection

According to.....: None
Type of protection.....: None

General

Direction of rotation.....: CW
Painting.....: RAL 9005
Nameplate.....: Multivoltage
Special packing.....: No
Special requirements.....: No

Rated power (kW)	30,0	29,0	36,0	35,0
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	53,5 31,0	55,5 32,0	53,5 31,0	55,5
Speed (rpm)	1480	1480	1780	1780
Power factor cos(phi)	0,85	0,86	0,85	0,87
Efficiency, 100/75/50 (%)	94,9/95,0/94,7	94,9/95,0/94,7	94,9/95,0/94,7	94,5/94,7/94,3
Ist/In	9,50	8,35	9,50	8,75
Full load torque (Nm)	194	188	194	188
Tst/Tn	2,60	2,42	2,60	2,26
Tmax/Tn	3,40	3,15	3,40	2,95
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45